

MAXIMO

MAXIMUM LIFE + MAXIMUM PROTECTION

MAXIMUM LIFE + MAXIMUM PROTECTION

Updated 9/15

SAE 0W-20 Full Synthetic SAE 5W-30 SN GF-5



Maximo engine oil offers ultimate protection for modern gasoline engines that start quicker, turn faster and run hotter. Maximo Full Synthetic is formulated to show improved high temperature deposit control and oxidation. Full Synthetic is made from a group III base oil and plus performance additives to offers improved performance over the former API service classification. Engineered to the high demands of turbocharged & high power, & propane engines in the latest model passenger cars & light duty trucks. Maximo is designed to flow at low temperatures to get to vital engine parts quickly in high efficiency gasoline engines using less oil consumption and improvements in fuel economy. Maximo Synthetic offers improved performance over the former API service classification & applies to MIL_L-46152E, FORD WSSS-M@C153-H, WSS-M2C930-A, GM-6048M & 6049M, Daimler Chrysler MS-6395, and more.

SAE GRADE SN		0W-20	5W-30
Specific Gravity@15.6°C (60°F)		0.846	0.850
Flash Point °C		210	200
Pour Point, °C		-51	-39
Viscosity Index		169	167
CCS Viscosity (D2270)	cP@-35°C	5600	----
	cP@-30	----	6300
Evaporative Loss, NOACK, wt. %		<15	<15
Sulfated Ash, weight%		0.92	0.92
Kinematic Viscosity	@ CST 40°C	46.3	57.0
	@ CST 100°C	8.7	10.4
Color		L3.5	3.0
Zinc, ppm		860	N/A
Phosphorous ,ppm		780	N/A
ILSAC		GF-5	GF-5
API Grade		SN	SN
5 gallon		F175-02	F175-53
55 gallon		F179-02	F179-53
Bulk		F170-02	F170-53

