

SYNTHETIC BLEND  
DIESEL

# MAXIMO

MAXIMUM LIFE + MAXIMUM PROTECTION  
MÁXIMA VIDA + MÁXIMA PROTECCIÓN



MAXIMO Synthetic Blend Diesel Engine Oil is a premium diesel engine oil meeting the requirements of diesel and gasoline engines requiring API (American Petroleum Institute) specifications CK-4, CJ-4, CI-4, CI-4+, CH-4 and SN. It is durable, long lasting oil approved for many applications.



- EXCELLENT WEAR PROTECTION
- EXCELLENT DEPOSIT CONTROL
- CLEAN ENGINE TECHNOLOGY
- HIGH TEMPERATURE STABILITY
- DESIGNED FOR SCR/EGR/DPF ENGINES

SAE GRADE	TYPICAL PROPERTIES	METHOD	15W-40 CK-4, CJ-4/SN	15W-40 CJ-4/SN
	Blend		Synthetic Blend	Synthetic Blend
	Gravity, °API	ASTM D287	30.55	32.73
	Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8732	0.865
	Viscosity @ 40°C cSt	ASTM D445	116.1	118
	Viscosity @ 100°C cSt	ASTM D445	15.66	15.7
	Viscosity Index	ASTM D2270	143	141
	Pour Point °C (°F)	ASTM D5950	-36°C (-33°F)	-36°C (-33°F)
	Cold Cranking Simulator at (°C), cP	ASTM D5293	5398 (-20)	5800 (-20)
	High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	4.3	4.2
	Noack Volatility, % loss	ASTM D6375	9	12
	Color	ASTM D1500	3	3
	Zinc, wt. %	ASTM D5185	0.127	0.127
	Phosphorus, wt. %	ASTM D5185	0.115	0.115
	Calcium, wt. %	ASTM D5185	0.105	0.105
	Sulfur, wt. %	ASTM D4951	0.32	0.32
	Sulfated Ash, wt. %	ASTM D874	0.99	.99
	Nitrogen, wt. %	ASTM D4629	0.105	0.105
	Pumping Viscosity at (°C), cP	ASTM D4684	21,600 (-25)	20,000 (-20)
	TBN, mgKOH/g	ASTM D2896	10	10
	Case Good 12/1 Quart bottles		F231-15	
	Case Good 3/1 Gallon bottles			F233-15
	5 Gallon Pail			F235-15
	55 Gallon Drum			F239-15
	Tote			
	Bulk			F230-15

Updated  
4/17

MaximoOil.com

205 NE 179 Street Miami, FL 33162 305-652-2944



**MADE IN USA**  
with both foreign  
and domestic  
components